



注：L 随整机长度而定，但最长不得超过4米。

⑪	GB93-87	弹垫 10	2																	
⑩	GB97.2-85	平垫 10	2																	
⑨	GB5782-86	螺栓M10x45	2																	
⑧	GB93-87	弹垫 16	3																	
⑦	GB97.2-85	平垫 16	3																	
⑥	GB5782-86	螺栓M16x35	2																	
⑤	GB93-87	弹垫 10	6																	
④	GB97.2-85	平垫 10	6																	
③	GB5780-86	螺栓M10x30	6																	
②	YF07.3	直角管接头M10x1	1																	
①	YF05.3	铜管接头M10x1	1																	

13	LSY163-217	观察孔盖	1	Q235																
12	LSY163-218	连接管φ194x6	1	20																
11	LSY163-211	吊耳	2	Q235																
10	LSY163-210	大叶片		16Mn																
9	LSY163-302	芯管	1	20																
8	LSY163-208	花键轴堵	2	Q235																
7	LSY163-207	内花键套	2	40Cr																
6	LSY163-206	中心花键轴	1	40Cr																
5	LSY163-205	吊座滑动轴承	1	锌基合金																
4	LSY163-204	轴承吊座	1	ZG270~500																
3	LSY163-203	过油螺栓	1	45																
2	LSY163-301	无缝钢管	1	20																
1	LSY163-201	管体连接法兰	2	Q235																

序号	代号	名称	数量	材料	单件重量	总计重量	备注
第二部分传动部装 LSY163-300							
标记	处数	更改文件号	签名	日期	阶段标记	重量	比例
设计	李连通		工艺				
校对	秦海波		标准				
审核	刘飞		批准				
				共张	第张		

